



Переход концентрический



- SDR 17
- удлиненный литой
- ел. сварка или встык
- PE 100 RC черный
- код : 067

Диаметр	Код	Маркеровка	da(OD) mm	d1 mm	s mm	L mm	s1 mm	Вес
75/63	70.067.7563.17	75/63 SDR17 ISO S-8	75	63	4,5	146	3,8	0.129
90/63	70.067.9063.17	90/63 SDR17 ISO S-8	90	63	5,4	172	3,8	0.199
90/75	70.067.9075.17	90/75 SDR17 ISO S-8	90	75	5,4	163	4,5	0.196
110/63	70.067.1163.17	110/63 SDR17 ISO S-8	110	63	6,6	182	3,8	0.297
110/90	70.067.1190.17	110/90 SDR17 ISO S-8	110	90	6,6	175	5,4	0.331
125/63	70.067.1263.17	125/63 SDR17 ISO S-8	125	63	7,4	187	3,8	0.375
125/90	70.067.1290.17	125/90 SDR17 ISO S-8	125	90	7,4	191,5	5,4	0.438
125/110	70.067.1211.17	125/110 SDR17 ISO S-8	125	110	7,4	193	6,6	0.483
140/125	70.067.1412.17	140/125 SDR17 ISO S-8	140	125	8,3	211	7,4	0.65
160/90	70.067.1690.17	160/90 SDR17 ISO S-8	160	90	9,5	215	5,4	0.76
160/110	70.067.1611.17	160/110 SDR17 ISO S-8	160	110	9,5	222	6,6	0.802
160/125	70.067.1612.17	160/125 SDR17 ISO S-8	160	125	9,5	227	7,4	0.852
160/140	70.067.1614.17	160/140 SDR17 ISO S-8	160	140	9,5	234	8,3	0.945
180/125	70.067.1812.17	180/125 SDR17 ISO S-8	180	125	10,7	270	7,4	1.26
180/160	70.067.1816.17	180/160 SDR17 ISO S-8	180	160	10,7	270	9,5	1.38
200/160	70.067.2016.17	200/160 SDR17 ISO S-8	200	160	11,9	253	9,5	1.54
225/160	70.067.2216.17	225/160 SDR17 ISO S-8	225	160	13,4	258	9,5	1.839
250/160	70.067.2516.17	250/160 SDR17 ISO S-8	250	160	14,8	318	9,5	2.762
250/200	70.067.2521.17	250/200 SDR17 ISO S-8	250	200	14,8	317	11,9	3.06
250/225	70.067.2522.17	250/225 SDR17 ISO S-8	250	225	14,8	312	13,4	3.36
280/250	70.067.2825.17	280/250 SDR17 ISO S-8	280	250	16,6	355	14,8	4.52
315/200	70.067.3120.17	315/200 SDR17 ISO S-8	315	200	18,7	375	11,9	5.4
315/225	70.067.3122.17	315/225 SDR17 ISO S-8	315	225	18,7	375	13,4	5.6
315/250	70.067.3125.17	315/250 SDR17 ISO S-8	315	250	18,7	375	14,8	5.76